
















PS 二線式單相相位控制器

圖號	圖號A	圖號B	圖號C	圖號D
參考圖				
尺寸	104x126x115 mm	104x110x155 mm	104x126x170 mm	140x126x170 mm
淨重	875g	1350g	1675g	2255g
圖號	圖號E	圖號F	圖號G	圖號H
參考圖				
尺寸	194x140x200 mm	133x110x155 mm	133x126x170 mm	175x126x170 mm
淨重	4240g	1650g	2000g	2575g
圖號	圖號I	圖號J	圖號K	圖號L
參考圖				
尺寸	235x140x200 mm	202x126x115 mm	202x110x155 mm	202x126x170 mm
淨重	4800g	1575g	1880g	2875g
圖號	圖號M	圖號N	圖號O	
參考圖				
尺寸	237x110x155 mm	237x126x170 mm	337x140x200 mm	
淨重	2200g	3435g	6775g	

訂購資訊：

品名：PS A BBB C D E

例如：PS 1 020 2 X A

A→	輸入方式
	1 4-20mA 基本型
	2 0-20mA
	3 0-5V
	4 1-5V
	5 0-10V
	6 2-10V
BBB→	額定負載電流
	020 20 A
	050 50 A
	100 100 A
	160 160 A
	200 200 A
C→	額定負載電壓
	1 110 Vac
	2 220 Vac
	3 380 Vac
	4 440 Vac
D→	特殊功能
	X 基本型
E→	圖號
	A 圖號A
	B 圖號B

產品規格

電流	A(av)	$I^2t(A^2s)$	圖號	推薦圖號
020	20A	310	A B	A
030	30A	770	A B	A
050	50A	1600	B C	B
070	70A	2700	C D	C
080	80A	3800	C D	D
100	100A	7400	E H	H
120	120A	10600	E H	H
160	160A	18000	O	
200	200A	29000	O	
300	300A	63000	O	