








SSR[AC-AC] 固態繼電器[AC-AC]

圖號	圖號A	圖號B	圖號C	圖號D
參考圖				
尺寸	67x48x33 mm	67x80x75 mm	75x50x83 mm	104x50x115 mm
淨重	130g	320g	270g	390g
圖號	圖號E	圖號F	圖號G	
參考圖				
尺寸	126x53x128 mm	104x85x115 mm	126x88x128 mm	
淨重	640g	690g	960g	

訂購資訊：

品名：SSR AA BB C D
 例如：SSR 22 15 A A

AA→	額定負載電壓
	22 低壓(100~260Vac)
	38 高壓(100~480Vac)
BB→	額定負載電流
	15 15A
	25 25A
	40 40A
	50 50A
C→	輸入方式
	A (交流電)
D→	圖號
	A 圖號A
	B 圖號B

產品規格

電流 / 模組	A(av)	$I^2t(A^2s)$	圖號	推薦圖號
15/T	15A	220	B C	B
25/T	25A	440	B C	B
40/T	40A	770	D F	D
15/D	15A	220	B C	B
30/D	30A	770	B D F	B
40/D	40A	1100	D F	D
50/D	50A	1600	D E F	D
60/D	60A	2700	D E F G	E
70/D	70A	3800	E G	E