
















圖號	圖號A	圖號B	圖號C	圖號D
參考圖				
尺寸	72x80x85 mm	72x105x125 mm	103x72x110 mm	110x105x125 mm
淨重	410g	590g	460g	700g
圖號	圖號E	圖號F	圖號G	圖號H
參考圖				
尺寸	140x85x132 mm	107x105x125 mm	145x105x125 mm	158x85x132 mm
淨重	780g	890g	1000g	1080g
圖號	圖號I	圖號J	圖號K	圖號L
參考圖				
尺寸	152x80x85 mm	187x72x110 mm	160x105x125 mm	180x105x125 mm
淨重	670g	880g	1170g	1500g
圖號	圖號M	圖號N	圖號O	圖號P
參考圖				
尺寸	207x72x110 mm	195x105x125 mm	215x105x125 mm	
淨重	1040g	1470g	1800g	

訂購資訊：

品名：SRSM A BBB C - D E F

例如：SRSM 2 015 H - D X A

A→	極
	2 3Φ2P
	3 3Φ3P
BBB→	額定負載電流
	015 15A
	025 25A
	030 30A
	040 40A
	050 50A
	060 60A
	070 70A
C→	額定負載電壓
	L (100~260Vac)
	H (100~480Vac)
D→	晶片
	D SCR
	T TRIAC
E→	特殊功能
	X 基本型
	1 過熱(OH)
F→	圖號
	A 圖號A
	B 圖號B

產品規格

電流 / 模組	A(r.m.s)	$I^2t(A^2s)$	圖號
015-T	15A	220	A
025-T	25A	310	A
040-T	40A	770	B
030-D	30A	770	B
050-D	50A	1600	D
060-D	60A	2700	F
070-D	70A	3800	G