






















SSC三相固態控制器 (TOKIWA)

圖號	圖號A	圖號B	圖號C	圖號D
參考圖				
尺寸	104x126x115 mm	104x110x155 mm	104x126x170 mm	140x126x170 mm
淨重	875g	1350g	1675g	2255g
圖號	圖號E	圖號F	圖號G	圖號H
參考圖				
尺寸	194x140x200 mm	133x110x155 mm	133x126x170 mm	175x126x170 mm
淨重	4240g	1650g	2000g	2575g
圖號	圖號I	圖號J	圖號K	圖號L
參考圖				
尺寸	235x140x200 mm	202x126x115 mm	202x110x155 mm	202x126x170 mm
淨重	4800g	1575g	1880g	2875g
圖號	圖號M	圖號N	圖號O	圖號P
參考圖				
尺寸	237x140x200 mm	317x140x200 mm	237x110x155 mm	237x126x170 mm
淨重	3675g	5600g	2200g	3435g
圖號	圖號Q	圖號R	圖號S	圖號T
參考圖				
尺寸	277x140x200 mm	358x140x200 mm	350x140x200 mm	468x140x200 mm
淨重	4235g	6160g	7000g	9400g

圖號	圖號U	圖號V		
參考圖				
尺寸	468x140x200 mm	648x190x215 mm		
淨重	9400g	14800g		

訂購資訊：

品名：SSC A BBB C D E F

例如：SSC 2 030 L X X A

A→	極
	2 兩極
	3 三極
B→	額定負載電流
	030 30A
	050 50A
	070 70A
	100 100A
	120 120A
	150 150A
	160 160A
	200 200A
	300 300A
	400 400A
C→	額定負載電壓
	L 低壓(100~260Vac)
	H 高壓(100~480Vac)
D→	加長型(附保險絲)
	X 不附保險絲
	L 附保險絲
E→	特殊功能
	X 基本型
	1 O.H
	2 O.H+斷線+欠相
	3 O.H+擊穿
	4 O.H+斷線+欠相+擊穿
	5 O.H+過流
F→	圖號
	A 圖號A
	B 圖號B

產品規格

品名	額定負載電流	$I^2t (A^2s)$	圖號	圖號(加長型)
2030	30A	770	A	
2050	50A	1600	C	
2070	70A	2700	H	
2080	80A	3800	H	
2100	100A	7400	I	
2120	120A	10600	I	
2160	160A	18000	S	
2200	200A	29000	S	
2300	300A	63000	T	
3030	30A	770	C	K
3050	50A	1600	H	O
3070	70A	2700	I	P
3080	80A	3800	I	Q
3100	100A	7400	I	Q
3120	120A	10600	I	Q
3160	160A	18000	U	
3200	200A	29000	U	
3300	300A	63000	V	