

z2 三相零位控制器 (直推式)

圖號	圖號A	圖號B	圖號C	圖號D
參考圖				
尺寸	104x126x115 mm	104x110x155 mm	104x126x170 mm	140x126x170 mm
淨重	875g	1350g	1675g	2255g
圖號	圖號E	圖號F	圖號G	圖號H
參考圖				
尺寸	194x140x200 mm	133x110x155 mm	133x126x170 mm	175x126x170 mm
淨重	4240g	1650g	2000g	2575g
圖號	圖號I	圖號J	圖號K	圖號L
參考圖				
尺寸	235x140x200 mm	202x110x155 mm	202x126x170 mm	237x140x200 mm
淨重	4800g	1880g	2875g	3675g
圖號	圖號M	圖號N	圖號O	圖號P
參考圖				
尺寸	237x110x155 mm	237x126x170 mm	277x140x200 mm	185x180x170 mm
淨重	2200g	3435g	4235g	2400g
圖號	圖號Q	圖號R	圖號S	圖號T
參考圖				
尺寸	235x180x170 mm	335x180x170 mm	435x180x180 mm	200x180x170 mm
淨重	3200g	4400g	5240g	2740g

圖號	圖號U	圖號V	圖號W	
參考圖				
尺寸	300x180x170 mm	350x180x170 mm	450x170x180 mm	
淨重	3840g	5040g	5880g	

訂購資訊：

品名：Z2 A BBB C D E F

例如：Z2 1 030 2 X X A

A→	輸入訊號
	1 4-20mA 基本型
	2 12Vdc
	3 24Vdc
	4 P.W.M
BBB→	額定負載電流
	020 20A
	030 30A
	100 100A
	120 120A
	200 200A
	300 300A
C→	額定負載電壓
	2 220Vac
	4 440Vac
D→	加長型(附保險絲)
	X 不附保險絲
	L 附保險絲
E→	特殊功能
	X 基本型
	1 欠相、過熱、警報接點
F→	圖號
	A 圖號A
	B 圖號B

產品規格

品名	A(av)	$I^2t(A^2s)$	圖號	圖號(加長型)
020	20A	310	A	
030	30A	770	B	J
050	50A	1600	G	J
070	70A	2700	H	M
080	80A	3800	H	N
100	100A	7400	I	N
120	120A	10600	I	O
160	160A	18000	U	
200	200A	29000	V	
300	300A	63000	W	